



# Shenzhen Absen Optoelectronic Co., Ltd.

## KLCOB1.5 V2- Specifications

Version: V20230807

Parameter		Value
Physical Parameter	LED Type	Flip-chip RGB
	Pixel Pitch (mm)	1.56
	Panel Dimensions (WxHxD)/(mm)	600x337.5x39.3
	Pixel Per Panel	384x216
	Panel Weight (kg)	4.3
	Panel Material	Die Casting Aluminum
	Module Dimensions (WxH)/(mm)	150x168.75
Optoelectronic Parameter	Brightness (nit)	600
	Refresh Rate (Hz)	3840
	Gray scale (Bit)	13
	Contrast Ratio	15000:1
	Color Temperature (K)	6500
	Viewing Angle (H/V) (°)	160/160
	Driving Type	1/54
	AC Operating Voltage (V)	100~240
	Power Consumption (Max./Avg.)(W/m <sup>2</sup> )	336/112
Application Parameter	Storage Temperature (°C)	-40~+60
	Operating Temperature (°C)	-10~+40
	Storage Humidity (RH)	10%~85%
	Operating Humidity (RH)	10%~80%
	IP Rating (Front/Rear)	IP40/IP21
	Module Maintenance	Front
	PSU & Others Maintenance	Front
	Panel Installation Type	Fixed
	Max Rigging QTY.	20
	Certificate	CCC,CE,ETL,FCC

Remark: Power consumption tolerance:  $\pm 15\%$ , according to the actual situation.

SHENZHEN ABSEN OPTOELECTRONIC CO.,LTD 2001-2022 ALL RIGHTS RESERVED